

FS20L7CSS



19.75" x 19.75" x 19.38" (H x W x D)

Commercially approved compact "cube" shaped all-freezer with a front-mounted lock and complete stainless steel exterior, capable of -20°C operation

Highlights:

Commercially approved for use in foodservice establishments

Compact "cube" size for easy placement above counters

-20° C capable for sensitive storage

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 and CalCode Compliant
Complete stainless steel exterior	Unit is fully wrapped in 304 grade stainless steel for durable luxury
Fully finished cabinet	Allows the unit to be used freestanding
Cube shaped	Square footprint for placement on top of counters
Factory installed lock	Keyed lock for a secure interior
-20° C capable	Operates at safe temperature for storage of select sensitive material
Manual defrost	Static cooling system for improved temperature stability
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials

FS20L7CSS Specifications:

Overview	
Height of Cabinet	19.75" (50 cm)
Width	19.75" (50 cm)
Depth	19.38" (49 cm)
Depth with door at 90°	37.88" (96 cm)
Capacity	1.6 cu.ft. (45 L)
Defrost Type	Manual
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	1.43
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	60.0 lbs. (27 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101008356
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.5" (37 cm)
Interior Width	15.5" (39 cm)
Interior Depth	15.0" (38 cm)
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	3.17 oz.
High Side PSI	250.0
Low Side PSI	88.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	7.0" (18 cm)

