

SCF1476PDC



48.5" x 53.25" x 27" (H x W x D)

Deluxe dipping cabinet with polycarbonate sneezeguard and digital thermostat

Highlights:

Deluxe dipping cabinet with fully assembled polycarbonate sneezeguard

ETL-S listed to NSF standards for use in commercial settings

Choice of gelato pans, tub holders, or novelty baskets

Product Features:

Polycarbonate sneezeguard	Durable sneezeguard with stainless steel support
Fluorescent light	Fully illuminates products for a tempting display
Digital thermostat	Set precise serving temperature with easy electronic controls, designed to operate between 0° and 20°F
Caster wheels	Heavy duty casters for smooth mobility
Fan-cooled compressor	Interior maintains even cooling so all contents stay cold
Manual defrost	Front located drain for easy defrosting
Factory installed lock	Keyed lock for secure interior
Aluminum interior	21" deep for maximum storage
Choice of storage accessories	Choose 3 gelato pan holders or 4 tub holders



SCF1476PDC Specifications:

Overview	
Height of Cabinet	48.5" (123 cm)
Width	53.25" (135 cm)
Depth	27.0" (69 cm)
Capacity	14.1 cu.ft. (399 L)
Defrost Type	Manual
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Sanitation	ETL-S
Amps	2.05
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	Sliding
Interior Height	25.63" (65 cm)
Interior Width	47.75" (121 cm)
Interior Depth	20.88" (53 cm)
Thermostat Type	Digital
Interior Light	Yes
Refrigerant Type	R134a
Refrigerant Amount	5.47 oz.
High Side PSI	250.0
Low Side PSI	88.0
Wheels	4
Compressor Step Height	10.5" (27 cm)
Compressor Step Width	12.25" (31 cm)
Temperature Range	0 to 20° F

