

# SCFF44FROST



33.88" x 18.5" x 21.38" (H x W x D)

DISCONTINUED: For a similar model, see the FS60MFROST

### Highlights:

Commercially approved for use in food service establishments

Operates at approximately 24° F to bring aluminum bottled beer just above the freezing point

Digital thermostat with external readout for easy and precise temperature control

### Product Features:

Commercially approved	ETL-S Listed and CalCode Compliant
24° F pre-set operation	Ideal temperature to hold beer in aluminum bottles at its coldest
Fully finished black cabinet	Allows the unit to be used freestanding
Stainless steel door	Professional style with a luxurious stainless steel door
Top-mounted compressor	Eliminates the usual compressor shelf to provide more storage room at the bottom of the unit; compressor is concealed behind sealed top compartment
Frost-free operation	Let the appliance do the work with a timer defrost that continuously prevents ice from forming inside
Digital thermostat	Precise temperature management at the touch of a button, with an external display for added convenience
Casters	Four sturdy casters are installed for smooth mobility and easy cleanup
Cantilevered shelf	Adjustable shelf can easily be set at any position to accommodate contents

# SCFF44FROST Specifications:

Overview	
Height of Cabinet	33.88" (86 cm)
Width	18.5" (47 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	38.0" (97 cm)
Defrost Type	Frost-Free
Door	SS/Decal
Cabinet	Black
US Electrical Safety	UL
Sanitation	ETL-S
Amps	2.3
Voltage/Frequency	115 V AC/60 Hz
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101021706
Freezer	
Door Swing	RHD
Reversible	No
Interior Height	20.13" (51 cm)
Interior Width	15.25" (39 cm)
Interior Depth	14.5" (37 cm)
Shelf Type	Wire
Shelf Qty	1
Adjustable Shelves	Yes
Thermostat Type	Digital
Interior Light	Yes
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	5.65 oz.
High Side PSI	186.0
Low Side PSI	88.0
Wheels	4

