

# SCR1300



73" x 23.63" x 23.5" (H x W x D)

Commercial full-sized beverage merchandiser with automatic defrost in slim width

### Highlights:

Full fluorescent light keeps all items on display to help increase impulse sales

Tropicalized glass door design keeps products well-preserved, even in hot temperatures

Factory installed lock offers added security

### Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments
Thin-line design	Limited space is no problem for our thin-line models, designed specifically for those hard-to-fit spots
Double pane tempered glass door	Tropicalized design protects contents from ambient hot temperatures
Automatic defrost	Reduced maintenance with auto defrost system
Adjustable shelves	Slide-out shelves with no clips for faster adjusting
Fluorescent lighting	Fully illuminates the interior on a convenient ON/OFF switch
Internal fan	Even circulation throughout the interior
Factory installed lock	Keyed lock for a secure interior
Reversible door*	Unit ships RHD. Door swing can be specified upon order or reversed in the field with an optional left-hand hinge



## SCR1300 Specifications:

Overview	
Height of Cabinet	73.0" (185 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Capacity	13.0 cu.ft. (368 L)
Defrost Type	Automatic
Door	Glass
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	5.4
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	220.0 lbs. (100 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101002729
Refrigerator Features	
Door Swing	RHD
Reversible	Reversible w/ Optional Hinge
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	5.2oz.
High Side PSI	430.0
Low Side PSI	87.0
Interior Light	Yes
Dimensions	
Interior Height	62.5" (159 cm)
Interior Width	19.25" (49 cm)
Interior Depth	17.25" (44 cm)
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	19.25" (49 cm)

Compressor Step Depth

6.0"



