accuc@ld

ARS1PV



21.5" x 17.5" x 19.75" (H x W x D)

Performance series Pharma-Vac 1 cu.ft. compact allrefrigerator for vaccine storage with antimicrobial silver-ion handle and hospital grade cord with 'green dot' plug

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Powder-coated handle with naturally occurring silver ions to help reduce germ spread

Product Features:

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Antimicrobial silver ion-coated handle	Powder-coated handle with naturally occurring silver ions to help reduce germ spread
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment
Open door alarm	Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)

accuc@ld

ARS1PV Specifications:

Overview	
Height of Cabinet	21.5" (55 cm)
Width	17.5" (44 cm)
Width with Door Open	18.0" (46 cm)
Depth	19.75" (50 cm)
Depth with Handle	21.5" (55 cm)
Depth with door at 90°	36.0" (91 cm)
Capacity	1.0 cu.ft. (28 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	61.0 lbs. (28 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101062945
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	
	Wire
Shelf Qty	
Shelf Qty Adjustable Shelves	3
	3 Yes
Adjustable Shelves	3 Yes Digital
Adjustable Shelves Thermostat Type	3 Yes Digital Interior
Adjustable Shelves Thermostat Type Fan Type	3 Yes Digital Interior
Adjustable Shelves Thermostat Type Fan Type Refrigerant Type	3 Yes Digital Interior R600a
Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	3 Yes Digital Interior R600a 0.71oz.
Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light	3 Yes Digital Interior R600a 0.71oz. Yes
Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range	3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C
Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level	3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C
Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Sound Level Dimensions	3 Yes Digital Interior R600a 0.71oz. Yes 2 to 8°C 42 dB



