accuc@ld

ACR45LCAL



31.5" x 19.5" x 22.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, frost-free with an internal fan, external digital controls and NIST calibrated thermometer, self-closing door, and lock

Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

High temperature alarm includes NIST calibrated external temperature readout (NIST certificate included)

Product Features:

Vaccine refrigerator	Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage
ADA compliant	Sized just under 32" high to allow installation under lower ADA compliant counters
Built-in capable	Front-breathing system allows the unit to be installed under cabinets with minimum clearance
Slim 20" width	Full 2.65 cu.ft. capacity inside conveniently slim footprint
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
NIST calibrated external temperature display	/ Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
Certificate of calibration included	Calibrated to NIST standards in our ISO/IEC 17025:2017 accredited laboratory, with a certificate included for your records
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines



accuc@ld

ACR45LCAL Specifications:

Height of Cabinet	31.5" (80 cm)
Width	19.5" (50 cm)
Depth	22.75" (58 cm)
Depth with Handle	23.63" (60 cm)
Depth with door at 90°	41.0" (104 cm)
Capacity	2.65 cu.ft. (75 L)
Defrost Type	Frost-Free
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	79.0 lbs. (36 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101076027
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	3
Adjustable Shelves	
Adjustable Shelves	Yes
Thermostat Type	Yes Digital
Thermostat Type	Digital Interior and
Thermostat Type Fan Type	Digital Interior and Exterior
Thermostat Type Fan Type Refrigerant Type	Digital Interior and Exterior R600a
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Digital Interior and Exterior R600a 0.99oz.
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI	Digital Interior and Exterior R600a 0.99oz. 270.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Digital Interior and Exterior R600a 0.99oz. 270.0 105.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty	Digital Interior and Exterior R600a 0.99oz. 270.0 105.0
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light	Digital Interior and Exterior R600a 0.99oz. 270.0 105.0 4 Yes
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range	Digital Interior and Exterior R600a 0.99oz. 270.0 105.0 4 Yes
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range Dimensions	Digital Interior and Exterior R600a 0.99oz. 270.0 105.0 4 Yes 2º to 8ºC
Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range Dimensions Interior Height	Digital Interior and Exterior R600a 0.99oz. 270.0 105.0 4 Yes 2º to 8ºC

Compressor Step Width	15.0" (38 cm)
Compressor Step Depth	4.75" (12 cm)



